

SWF / TB - W L 9 15 - 100

Series	Y-Stroke
M/C Type	No. of Heads
Head Interval	No. of Colors

Specifications		
Speed	Standard (6 heads or more)	1,200 rpm [less than 8,400 mm(Length)]
		1,100 rpm [8,400 mm(Length) or more and less than 10,000 mm(Length)]
		1,000 rpm [10,000 mm(Length) or more]
	Standard (less than 6 heads)	1,000 rpm
	Taping Head	1,000 rpm [Taping & Zigzag]
500 rpm [Coiling]		
Stitching Length		0.1 ~ 12.7 mm
Motor	Main	Servo Motor x 1
	X-Y	Servo Motor x 2 (6heads or more)
		Step Motor x 2 (less than 6heads)
Electricity		1-Phase 200V, 220V, 240V [50/60Hz]
		3-Phase 200V, 220V, 240V, 350V, 380V, 415V [50/60Hz] (6heads or more)
Power Consumption		1.5 kW
Bobbin Winder		Standard
Upper Thread Holding Unit		Standard
Lubrication System		Auto Lubrication System
Operation Box		Standard : Color LCD Touch Screen
Hook		Standard Hook
Memory Capacity		Standard : 4,000,000 stitches * Possible to change by additional functions
Memory Media		USB Memory Stick
Safety Device		Standard : Emergency Stop, Error Code Message
Optional Device		SQ30/SQ31D, SQ31B, SQ35, SQ41i, Cording, Boring

Division of Model									
Model	Head Interval [mm]	Color	Head	Y-Stroke [mm]	Emb. Space [mm]		Machine Size [mm]		
					Each Head	All Head	Length	Width	Height
TB-WJ614-100	450	6 + 1	14 + 14	1,000	450 x 1,000	6,750 x 1,000	8,468.5	2,498.5	1,827
TB-WJ614-120	450	6 + 1	14 + 14	1,200	450 x 1,200	6,750 x 1,200	8,468.5	2,848.5	1,827
TB-WL906-120	550	9 + 1	6 + 6	1,200	550 x 1,200	3,300 x 1,200	5,650	2,848.5	1,827
TB-WL908-75	550	9 + 1	8 + 8	750	550 x 750	4,400 x 750	6,750	1,950	1,727
TB-WL910-120	550	9 + 1	10 + 10	1,200	550 x 1,200	5,500 x 1,200	7,850	2,848.5	1,727
TB-WL912-75	550	9 + 1	12 + 12	750	550 x 750	6,600 x 750	8,950	1,958.5	1,827
TB-WL912-100	550	9 + 1	12 + 12	1,000	550 x 1,000	6,600 x 1,000	8,950	2,498.5	1,827
TB-WL912-120	550	9 + 1	12 + 12	1,200	550 x 1,200	6,600 x 1,200	8,950	2,848.5	1,827
TB-WL915-100	550	9 + 1	15 + 15	1,000	550 x 1,000	8,250 x 1,000	10,650	2,509	1,827
TB-WL915-120	550	9 + 1	15 + 15	1,200	550 x 1,200	8,250 x 1,200	10,650	2,848.5	1,827
TB-WN902-100	660	9 + 1	2 + 2	1,000	660 x 1,000	1,320 x 1,000	4,105	2,486	1,727
TB-WN904-75	660	9 + 1	4 + 4	750	660 x 750	2,640 x 750	5,100	1,950	1,727
TB-WN904-100	660	9 + 1	4 + 4	1,000	660 x 1,000	2,640 x 1,000	5,100	2,486	1,727
TB-WN906-120	660	9 + 1	6 + 6	1,200	660 x 1,200	3,960 x 1,200	6,510	2,848.5	1,727

We can make some modification for improvements without previous notice.



TB SERIES

Lock-stitch taping & coiling automatic embroidery machines

The Best Value
by Reliable High-speed



SUNSTAR CO., LTD.

Head office #178-67, GAJWA-DONG, SEO-GU, INCHEON, KOREA
tel +82[0]32-580-5980-93 fax +82[0]32-579-8350-51 www.swfkorea.com



For W24H service
www.sunstarcs.com

